


Data sheet

Ecoguss project drain, press. fl. DN 80, horizontal, Design cover



Article information

article number: 48783.63
 EAN code: 4026092033463
 Price group: 40

Product advantages

- Scientifically confirmed sound protection effect
- Highest fire protection standards

Description

The Ecoguss project drain is used for point drainage and is equipped with a pressure sealing flange as well as a removable odour trap, a lip seal and a temporary protective cover. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

General features

Standard	EN 1253-1
Nominal size (DN)	80
Outer diameter (OD)	83 mm
Odour trap	included

Version

System	125
Waterproofing layer on the upper section	Connection flange
Waterproofing layer on the drain body	Press sealing flange (suitable for creating watertight seals)
Sealing water height	50 mm

Dimensions

Vertical adjustment	
Net weight	2.61 kg
Gross weight	2.98 kg
Diameter	273 mm
Type of height adjustability	vertically adjustable upper section
Length	273 mm
Width	273 mm
Packaging dimension: length	400 mm
Packaging dimension: width	300 mm
Packaging dimension: height	400 mm

Tank/drain body

Number of outlets	1
Material of drain body	Ecoguss resistant
Socket version	lateral

Coverage features

Type of cover	Design cover
Cover material	Stainless steel 14301
Colour of cover	silver
Width of cover	120 mm
Length of cover	120 mm
Surface	ground
Frame material	Stainless steel 14301
Locking	Lock & Lift
Load class	L 15 (EN 1253-1)
Grating design	Kessel
Slip resistance class	R9 according to DIN 51130; C according to DIN 51097
Rim width	132 mm
Rim length	132 mm
Max. flooring height	16 mm
Upper section	vertically adjustable
Shape of upper section	square
Upper section material	ABS