Data sheet

Ecoguss drain body Press. fl., DN 80, vertical, without OT



Article information

article number: 48889
EAN code: 4026092038215
Price group: 40

Product advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss drain body, in combination with a stainless steel, Ecoguss and recycled polymer upper section, is used for point drainage and is fitted with a temporary protective cover.

The recyclable composite material Ecoguss meets the highest sound insulation requirements, is permanently resistant to 350 aggressive media as per the resistance list, is temperature-resistant and has a permanently corrosion-free surface. It is briefly flame-resistant from 100 to 400 degrees Celsius.

The pressure sealing flange, with stainless steel bolts and screws, is designed for clamping or welding on bitumen and polymer-bitumen membranes, as well as polymer and elastomer waterproofing sheets. For watertight waterproofing layers, only waterproofing sheets tested by the manufacturer may be used. The outlet spigot is suitable for connection to SML cast iron pipes. It includes a connection option for equipotential bonding.

General features

Standard	EN 1253-2
Nominal size (DN)	80
Outer diameter (OD)	83 mm
Approval	Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-1719_V

Version

System	125
Waterproofing layer on the drain body	Press sealing flange (suitable for creating watertight seals)
Sealing water height	50 mm

Dimensions

Vertical adjustment	|
Net weight	1.98 kg
Gross weight	2.27 kg
Diameter	273 mm
Height	217 mm
Packaging dimension: length	280 mm
Packaging dimension: width	280 mm
Packaging dimension: height	260 mm

Tank/drain body

Number of outlets	1
Material of drain body	Ecoguss resistant
Socket version	vertical