Data sheet

Light liquid trap DN 100, slot grat., with backw. Prot-



Article information

article number: 52101
EAN code: 4026092029770
Price group: 10

Product advantages

- Blocks the path of light liquids in the event of an accident/emergency
- Including odour trap

Description

The light liquid trap made of polymer is suitable for floor slab installation and is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

General features

Standard	EN 13564
Nominal size (DN)	100
Outer diameter (OD)	110 mm
Backwater protection	Type 5
Odour trap	included

Version

Contents of sludge trap	yes
Sealing water height	50 mm
Discharge rate (l/s) with 20 mm threshold	1
Mechanical backwater flaps	2

Dimensions

Vertical adjustment	30|90 mm
Net weight	2.55 kg
Gross weight	2.88 kg
Cutout dimension, width	250 mm
Cutout dimension, length	400 mm
Installation depth	216|276 mm
Type of height adjustability	vertically adjustable upper section
Length	320 mm
Width	243 mm
Packaging dimension: length	380 mm
Packaging dimension: width	295 mm
Packaging dimension: height	257 mm

Tank/drain body

Material of drain body	Polymer

Coverage features

Type of cover	Slotted cover
Cover material	Polymer
Colour of cover	black
Width of cover	188 mm
Length of cover	188 mm
Load class	K 3 (EN 1253-1)
Rim width	200 mm
Rim length	200 mm
Shape of upper section	square
Upper section material	Polymer
Contents of sludge trap	yes