Data sheet

Ferrofix floor drain press, fl. DN 70, horiz., Slotted grating



Article information

article number: 54200.61
EAN code: 4026092056547
Price group: 70

Product advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- High flow rate

Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a pressure sealing flange as well as a removable odour trap made of stainless steel, a lip seal and a temporary protective cover. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only membranes tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

General features

Standard	EN 1253-1
Nominal size (DN)	70
Outer diameter (OD)	78 mm
Odour trap	included

Version

System	125
Waterproofing layer on the upper section	Connection flange
Waterproofing layer on the drain body	Press sealing flange (suitable for creating watertight seals)
Sealing water height	50 mm

Dimensions

Vertical adjustment	|
Net weight	2.77 kg
Gross weight	3.4 kg
Type of height adjustability	vertically adjustable upper section
Length	273 mm
Width	273 mm
Packaging dimension: length	400 mm
Packaging dimension: width	300 mm
Packaging dimension: height	400 mm

Tank/drain body

Number of outlets	1
Material of drain body	Stainless steel 14301
Socket version	lateral

Coverage features

Type of cover	Slotted cover
Cover material	Stainless steel 14301
Width of cover	138 mm
Length of cover	138 mm
Locking	screwed
Load class	L 15 (EN 1253-1)
Slip resistance class	R11 according to DIN 51130; C according to DIN 51097
Rim width	150 mm
Rim length	150 mm
Upper section	vertically adjustable
Shape of upper section	square
Upper section material	ABS