Data sheet

Floor/roof drain Ferrofix DN 100, horiz., Slotted grating, SST



Article information

article number: 54420.20
EAN code: 4026092056455
Price group: 70

Product advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- High flow rate

Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap made of stainless steel, a lip seal and a temporary protective cover. The outlet socket is suitable for connection to SML cast iron pipes.

General features

Standard	EN 1253-1
Nominal size (DN)	100
Outer diameter (OD)	110 mm
Odour trap	included

Version

System	125
Waterproofing layer on the upper section	Connection flange
Waterproofing layer on the drain body	Connection flange
Sealing water height	50 mm

Dimensions

Vertical adjustment	|
Net weight	4.21 kg
Gross weight	4.56 kg
Type of height adjustability	vertically adjustable upper section
Length	196 mm
Width	142 mm
Packaging dimension: length	390 mm
Packaging dimension: width	190 mm
Packaging dimension: height	310 mm

Tank/drain body

Number of outlets	1
Material of drain body	Stainless steel 14301
Socket version	lateral

Coverage features

Type of cover	Slotted cover
Cover material	Stainless steel 14301
Width of cover	138 mm
Length of cover	138 mm
Locking	unlocked
Load class	L 15 (EN 1253-1)
Rim width	150 mm
Rim length	150 mm
Upper section	vertically adjustable
Upper section material	Stainless steel 14301