Data sheet

Drain body Ferrofix, one-p, GF15 DN 100, vert., 206x206, grated cover L15



Article information

article number: 55147
EAN code: 4026092107720
Price group: 70

Product advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel

Description

The one-piece Ferrofix System 185 stainless steel floor drain is used for point drainage and is equipped with a removable odour trap, sludge bucket and grated cover. The floor drain is suitable for thin-layered floorings (e.g. epoxy resin) and has an all-round adhesive rim (15 mm deep and 50 mm folded outwards). The outlet socket is suitable for connection to SML cast iron pipes. With a drainage capacity 2.4 l/s with 20 mm build-up.

General features

Material	Stainless steel 14301
Outlet	vertical
Glued flange height	15 mm
Odour trap	included

Version

System	185
Contents of sludge trap	yes
Waterproofing layer on the upper section	Adhesive flange (suitable for moisture barriers)
Sealing water height	50 mm
Discharge rate (l/s) with 20 mm threshold	2.5
Outlet	vertical

Dimensions

Vertical adjustment	|
Net weight	0 kg
Gross weight	0 kg
Length	206 mm
Width	206 mm
Height	320 mm
Packaging dimension: length	0 mm
Packaging dimension: width	0 mm
Packaging dimension: height	0 mm

Tank/drain body

Number of outlets	1
Outlet nominal size (DN)	100
Socket version	vertical

Coverage features

Type of cover	Slotted cover
Cover material	Stainless steel 14301
Load class	L 15 (EN 1253-1)
Grating material	304 stainless steel
Max. flooring height	15 mm
Shape of upper section	square
Contents of sludge trap	yes

Cover

Grating material	304 stainless steel