Data sheet

Staufix FKA conversion kit DN 100-200, fr. 01/2011, 5 m cable

Article information

article number: 80093
EAN code: 4026092048245
Price group: 30

Product advantages

Description

The conversion kit is equipped with a motor-driven closure system, which is closed automatically in the event of backwater. A second closure system serves as an emergency closure to be closed by hand.

The station is controlled by a user-friendly control unit, which is optionally integrated in the building management system via a potential-free contact, or alarm and collective fault messages can be output via a GSM interface.

The conversion kit is used to retrofit Staufix FKA and Controlfix for the Staufix FKA backwater valve.

General features

Standard	EN 13564
Nominal size (DN)	100-200
Note on nominal size	Hydraulics correspond to DN 150
Type of wastewater	for wastewater with and without sewage
Installation situation	floor slab installation
Backwater protection	Type 3
Type de protection moteur	IP 68 (3m/48h)
Cable length	5 m

Dimensions

Net weight	5.83 kg
Gross weight	6.79 kg
Packaging dimension: length	600 mm
Packaging dimension: width	400 mm
Packaging dimension: height	420 mm

Control

Control unit	Comfort
Alarm sensor	optical probe
Level measurement instrument	optical probe
Type of level measurement	optical
Protection class control unit	IP 54
Length of mains cable for control unit	1.4 m
Potential-free contact	optional
GSM interface	yes
USB interface	yes
Log book function	yes
Multi-line display	yes
Battery buffering	yes
Self-diagnosis system (SDS)	yes