Data sheet

Grease separat. EasyClean Modular free, NS 1, Standard, 2-part

Article information

article number: 93001
EAN code: 4026092030875
Price group: 60

Product advantages

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

General features

Material	PE
Installation situation	free-standing installation
Delivery state	Installation-ready (connection parts must be connected on site)
Tightness	odour-tight

Version

Chamber system	two-piece chamber
Disposal variant	Standard
Shredder-Mix-System	no
Inspection window	no
Nominal size (NS)	1
SonicControl	no
Refill inlet in accordance with DIN 1988	no
Type of disposal	manual with suction hose

Dimensions

Net weight	41.5 kg
Gross weight	51 kg
Height tank bottom up to centre section	648 mm
Height centre section to top edge of tank	340 mm
Set-up area, length	1100 mm
Set-up area, width	1012 mm
Set-up area, height	988 mm
Packaging dimension: length	1200 mm
Packaging dimension: width	1100 mm
Packaging dimension: height	1140 mm

Tank/drain body

Distance pipe bottom outlet to tank bottom	415 mm
Distance pipe bottom inlet to tank bottom	485 mm
Outlet nominal size (OD)	110 mm
Outlet nominal size (DN)	100
Inlet nominal size (OD)	110 mm
Inlet nominal size (DN)	100
Connection inlet/outlet sockets	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features

Type of cover	Cover
Cover material	Polymer
Colour of cover	black
Locking	Quick-release closure
Tightness	odour-tight

Control

Control unit	no

Separator contents	100 l
Total volume	200 l
Contents of sludge trap	100 l
Storage quantity of grease	40 l