Data sheet

Grease separator EasyClean free NS 2, Standard, Ref. in., Insp. Win., SC

Article information

article number: 93002.32
EAN code: 4026092063422
Price group: 60

Product advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

General features

Material	PE
Installation situation	free-standing installation
Delivery state	Installation-ready (connection parts must be connected on site)
Tightness	odour-tight

Version

Disposal variant	Standard
Shredder-Mix-System	no
Inspection window	yes
Nominal size (NS)	2
SonicControl	yes
Refill inlet in accordance with DIN 1988	yes
Type of disposal	manual with suction hose
Load-bearing capacity (DIN 19901)	F3

Dimensions

Net weight	98.5 kg
Gross weight	128.5 kg
Set-up area, length	1736 mm
Set-up area, width	674 mm
Set-up area, height	1434 mm
Required access area, length	1500 mm
Required access area, width	674 mm
Required access area, height	1434 mm
Packaging dimension: length	1900 mm
Packaging dimension: width	1050 mm
Packaging dimension: height	1700 mm

Tank/drain body

Distance pipe bottom outlet to tank bottom	985 mm
Distance pipe bottom inlet to tank bottom	1055 mm
Outlet nominal size (OD)	110 mm
Outlet nominal size (DN)	100
Inlet nominal size (OD)	110 mm
Inlet nominal size (DN)	100
Connection inlet/outlet sockets	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features

Type of cover	Cover
Cover material	Polymer
Colour of cover	violet
Locking	Quick-release closure
Tightness	odour-tight

Control

Control unit	no

Separator contents	400 l
Total volume	600 l
Contents of sludge trap	200 l
Storage quantity of grease	100 l