Data sheet

Grease separator EasyClean free NS 3, Direct, Refill in., Insp. win., SC

Article information

article number: 93003.32/D
EAN code: 4026092063736
Price group: 60

Product advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

General features

Material	PE
Standard	EN 1825: 2004
Installation situation	free-standing installation
Delivery state	Installation-ready (connection parts must be connected on site)
Scope of delivery	Storz-B coupling R 2 1/2" for disposal vehicle connection
Tightness	odour-tight

Version

Disposal variant	Direct
Shredder-Mix-System	no
Inspection window	yes
Nominal size (NS)	3
SonicControl	yes
Disposal system	Disposal connection
Refill inlet in accordance with DIN 1988	yes
Type of disposal	manual
Load-bearing capacity (DIN 19901)	F3

Dimensions

Net weight	97 kg
Gross weight	127 kg
Set-up area, length	1736 mm
Set-up area, width	706 mm
Set-up area, height	1434 mm
Required access area, length	1500 mm
Required access area, width	680 mm
Required access area, height	1434 mm
Packaging dimension: length	1900 mm
Packaging dimension: width	1050 mm
Packaging dimension: height	1520 mm

Tank/drain body

Nominal pressure (PN)	10
Pressure pipe connection (DN)	65
Pressure pipe connection (OD)	75 mm
Distance pipe bottom outlet to tank bottom	985 mm
Distance pipe bottom inlet to tank bottom	1055 mm
Outlet nominal size (OD)	110 mm
Outlet nominal size (DN)	100
Inlet nominal size (OD)	110 mm
Inlet nominal size (DN)	100
Connection inlet/outlet sockets	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Servicing opening	420 mm

Coverage features

Type of cover	Cover
Cover material	Polymer
Colour of cover	violet
Locking	Quick-release closure
Tightness	odour-tight

Control

Control unit	no

Separator contents	300 l
Total volume	600 l
Contents of sludge trap	300 l
Storage quantity of grease	120 l