Data sheet

Grease separator EasyClean free NS 10, Mix, Inspec. window, SonicControl

Article information

article number: 93010.32/DS
EAN code: 4026092068946
Price group: 60

Product advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Simple control
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. The innovative Shredder-Mix-System with integrated macerating system is responsible for homogenising and circulating the tank contents. Cleaning is carried out by an exterior pump which can be disconnected from the tank by a shut-off valve. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. A direct disposal pipe socket is available for odour-neutral manual disposal. 20 year polyethylene warranty.

General features

Material	PE
Standard	EN 1825: 2004
Installation situation	free-standing installation
Delivery state	Installation-ready (electrical components, connection parts must be connected on site)
Scope of delivery	Storz-B coupling R 2 1/2" for disposal vehicle connection
Tightness	odour-tight

Version

Shut-off valve	yes
Disposal variant	Mix
Shredder-Mix-System	yes
Inspection window	yes
Nominal size (NS)	10
SonicControl	yes
Disposal system	Disposal connection
Refill inlet in accordance with DIN 1988	yes
Type of disposal	manual cleaning system
Water supply	1 screw-type valve 1"
Load-bearing capacity (DIN 19901)	F3

Dimensions

Net weight	249.5 kg
Gross weight	292.5 kg
Set-up area, length	2822 mm
Set-up area, width	1108 mm
Set-up area, height	1932 mm
Required access area, length	2590 mm
Required access area, width	940 mm
Required access area, height	1678 mm
Length	2822 mm
Width	1108 mm
Height	1932 mm
Packaging dimension: length	2850 mm
Packaging dimension: width	1150 mm
Packaging dimension: height	1700 mm

Tank/drain body

Nominal pressure (PN)	10
Pressure pipe connection (DN)	65
Pressure pipe connection (OD)	75 mm
Distance pipe bottom outlet to tank bottom	1185 mm
Distance pipe bottom inlet to tank bottom	1255 mm
Outlet nominal size (OD)	160 mm
Outlet nominal size (DN)	150
Inlet nominal size (OD)	160 mm
Inlet nominal size (DN)	150
Connection inlet/outlet sockets	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Servicing opening	420 mm

Coverage features

Type of cover	Cover
Cover material	Polymer
Colour of cover	violet
Locking	Quick-release closure
Tightness	odour-tight

Pumping device

Pump	SPF 300 KE 2.0
Number of pumps	1
Weight, pump	44 kg
Connection type	Direct connection
Protection class	I
Insulation class	F
Cos phi - power factor	0.87
Protection class (pump)	IP 55
Temperature monitoring	integrated
Max. temperature (permanent) of conveyed material	40 °C
Max. pumping capacity	60 m³/h
Max. pumping height	17 m
Speed	2850 U/min
Power P1	3.6 kW
Power P2	3 kW
Operating mode	S2 - 30 min.
Type of pump connection cable	H07RN-F 7G 1.5 mm²
Impeller type	Radial impeller with macerating system
Length of mains cable for pump	5 m
Rated current	6,2| A

Control

Control unit	yes
Type of fuse required (RCD)	30 mA
Mains frequency	50 Hz
Operating voltage	400 V
Connection type	Direct connection
Rated current	|

Separator contents	900 l
Total volume	1900 l
Contents of sludge trap	1000 l
Storage quantity of grease	400 l