Data sheet

Grease separator EasyClean ground NS 10, Standard, 1120-1740 mm, Class D

Article information

article number: 93010/170D
EAN code: 4026092073339
Price group: 60

Product advantages

- Vertically adjustable upper section with odour-tight cover plates in various load classes
- Waterproof, resistant to aggressive wastewater
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via one or several service access covers. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

General features

Material	PE
Standard	EN 1825: 2004
Installation situation	underground installation
Delivery state	Installation-ready (connection parts must be connected on site)
Tightness	odour-tight and surface water resistant

Version

Note on installation depth	Version for deeper installation
Chamber system	Cistern
Disposal variant	Standard
Shredder-Mix-System	no
Inspection window	no
Nominal size (NS)	10
SonicControl	no
Refill inlet in accordance with DIN 1988	no
Type of disposal	manual with suction hose
Load-bearing capacity (DIN 19901)	E4

Dimensions

Net weight	488 kg
Gross weight	510 kg
Groundwater resistant from lower edge of base section	1320 mm
Diameter	659 mm
DSC	700|1.500
T-DSC	220
Max. length	3062 mm
Installation depth	1120|1740 mm
Type of height adjustability	vertically adjustable upper section, can be tilted by 5 degrees
Required access area, length	2910 mm
Required access area, width	1200 mm
Packaging dimension: length	3062 mm
Packaging dimension: width	2150 mm
Packaging dimension: height	1787 mm

Tank/drain body

Distance pipe bottom outlet to tank bottom	1030 mm
Distance pipe bottom inlet to tank bottom	1100 mm
Outlet nominal size (OD)	160 mm
Outlet nominal size (DN)	150
Inlet nominal size (OD)	160 mm
Inlet nominal size (DN)	150
Connection inlet/outlet sockets	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Clear width of entry (LW)	800 mm

Coverage features

Type of cover	Cover plate
Cover material	Grey iron
Colour of cover	black
Height of cover	121 mm
Locking	locked
Load class	D 400 (EN 124)
Tightness	odour-tight and surface water resistant

Control

Control unit	no

Separator contents	1600 l
Total volume	2600 l
Contents of sludge trap	1000 l
Storage quantity of grease	400 l