Data sheet

Grease separator EasyClean free NS 15, Direct

Article information

article number: 93015.01/D
EAN code
Price group: 60

Product advantages

- Low-maintenance operation
- Odour-reduced disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. 20 year polyethylene warranty.

General features

Material	PE
Standard	EN 1825: 2004
Delivery state	Installation-ready (connection parts must be connected on site)
Scope of delivery	Storz-B coupling R 2 1/2" for disposal vehicle connection
Tightness	odour-tight

Version

Disposal variant	Direct
Shredder-Mix-System	no
Inspection window	no
Nominal size (NS)	15
SonicControl	no
Refill inlet in accordance with DIN 1988	no
Type of disposal	manual
Load-bearing capacity (DIN 19901)	F3

Dimensions

Net weight	0 kg
Gross weight	0 kg
Set-up area, length	3560 mm
Set-up area, width	1350 mm
Set-up area, height	1655 mm
Required access area, length	3300 mm
Required access area, width	1350 mm
Required access area, height	1625 mm
Packaging dimension: length	0 mm
Packaging dimension: width	0 mm
Packaging dimension: height	0 mm

Tank/drain body

Nominal pressure (PN)	10
Pressure pipe connection (DN)	65
Pressure pipe connection (OD)	75 mm
Distance pipe bottom outlet to tank bottom	1130 mm
Distance pipe bottom inlet to tank bottom	1200 mm
Outlet nominal size (OD)	200 mm
Outlet nominal size (DN)	200
Inlet nominal size (OD)	200 mm
Inlet nominal size (DN)	200
Connection inlet/outlet sockets	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features

Type of cover	Cover
Cover material	Polymer
Colour of cover	black
Locking	Quick-release closure
Tightness	odour-tight

Control

Control unit	no

Separator contents	1100 l
Total volume	2600 l
Contents of sludge trap	1500 l
Storage quantity of grease	600 l