Data sheet

Grease separator EasyClean free NS 30, Standard

Article information

article number: 93030-06
EAN code: 4026092103197
Price group: 60

Product advantages

- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

General features

Material	PE
Standard	EN 1825: 2004
Installation situation	free-standing installation
Delivery state	Installation-ready (connection parts must be connected on site)
Tightness	odour-tight

Version

Disposal variant	Standard
Shredder-Mix-System	no
Inspection window	no
Nominal size (NS)	30
SonicControl	no
Refill inlet in accordance with DIN 1988	no
Type of disposal	manual with suction hose
Load-bearing capacity (DIN 19901)	F3

Dimensions

Net weight	500 kg
Gross weight	500 kg
Diameter	630 mm
Set-up area, length	5160 mm
Set-up area, width	1280 mm
Set-up area, height	1625 mm
Required access area, length	5160 mm
Required access area, width	1280 mm
Required access area, height	1625 mm
Length	5160 mm
Width	1600 mm
Height	1625 mm
Packaging dimension: length	5160 mm
Packaging dimension: width	1280 mm
Packaging dimension: height	1625 mm

Tank/drain body

Distance pipe bottom outlet to tank bottom	1170 mm
Distance pipe bottom inlet to tank bottom	1240 mm
Outlet nominal size (OD)	250 mm
Outlet nominal size (DN)	250
Inlet nominal size (OD)	250 mm
Inlet nominal size (DN)	250
Connection inlet/outlet sockets	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features

Type of cover	Cover
Cover material	Polymer
Colour of cover	black
Locking	Quick-release closure
Tightness	odour-tight

Control

Control unit	no

Separator contents	2250 l
Total volume	5250 l
Contents of sludge trap	3000 l
Storage quantity of grease	1200 l