Data sheet

Coalescence separator EasyOil NS 3, class I, without sludge trap

Article information

article number: 99830
EAN code: 4026092097458
Price group: 60

Product advantages

- Permanent leak tightness up to op edge of the container
- Resistant to and suitable for up to 100 % share of biodiesel
- Suitable for filling stations with high-performance filling pumps, E10 and biodiesel fuels

Description

The light liquid separator is suitable for free-standing installation in frost-protected rooms and is equipped with a removable coalescence insert. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap (optional) and an automatic closure device. The odour-tight cover enables easy access for cleaning and maintenance work.

An inlet and outlet connection on site is possible with PE-HD pipes according to DIN 19537, PVC-KG pipes according to DIN 19534 and PP or AS on pipe spigots (PE) fitted at the factory. The applicable standards must be observed when selecting the appropriate seals and pipe materials.

20-year polyethylene warranty.

General features

Material	PE
Standard	EN 858
Installation situation	free-standing installation
Separator class	I

Version

Nominal size (NS)	3

Dimensions

Net weight	0 kg
Gross weight	0 kg
Length	1360 mm
Width	1300 mm
Height	750 mm
Packaging dimension: length	0 mm
Packaging dimension: width	0 mm
Packaging dimension: height	0 mm

Tank/drain body

Distance pipe bottom outlet to tank bottom	390 mm
Distance pipe bottom inlet to tank bottom	410 mm
Outlet nominal size (OD)	110 mm
Outlet nominal size (DN)	110
Inlet nominal size (OD)	110 mm
Inlet nominal size (DN)	110

Coverage features

Colour of cover	black
Total volume	415 l
Storage quantity of light liquid	78 l