Data sheet

Backwater valve Staufix DN 125, exposed, Type 1

Article information

article number: 720125
EAN code: 4026092076057
Price group: 10

Product advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

General features

Colour	black
Standard	EN 13564
Nominal size (DN)	125
Outer diameter (OD)	125 mm
Type of wastewater	without sewage
Installation situation	exposed drainage pipe
Delivery state	installation-ready
Backwater protection	Type 1

Version

Emergency closure	yes
Mechanical backwater flaps	1

Dimensions

Net weight	3.1 kg
Gross weight	5.7 kg
Vertical drop between inlet and outlet	8 mm
Length	511 mm
Width	216 mm
Height	306 mm
Packaging dimension: length	524 mm
Packaging dimension: width	222 mm
Packaging dimension: height	265 mm

Coverage features

Type of cover	Lockable cover
Cover locking	One-handed closure