Data sheet

# Backwater valve Staufix DN 90, Floor slab, tileable, Type 2 R




## Article information

article number: 730090.10XR
EAN code: 4026092076330
Price group: 10

## Product advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

## Description

The backwater valve for wastewater with and without sewage (ÖNORM Austria) is equipped with two mechanical flaps that close automatically in the event of backwater. One flap also serves as a manually lockable emergency closure. Thanks to the modular KESSEL system, existing systems can be easily converted to the StaufixControl backwater valve.

## General features

| | |
|---|---|
| Colour | black |
| Standard | EN 13564 |
| Nominal size (DN) | 90 |
| Outer diameter (OD) | 90 mm |
| Type of wastewater | containing faecal matter (excepterion: Germany faecal-free) |
| Installation situation | floor slab installation |
| Delivery state | Installation-ready (connection parts must be connected on site) |
| Backwater protection | Type 2 |
| Tightness | surface water resistant |

## Version

| | |
|---|---|
| Stainless steel flap as rat protection | yes |
| Emergency closure | yes |
| Mechanical backwater flaps | 2 |

## Dimensions

| | |
|---|---|
| Net weight | 5.95 kg |
| Gross weight | 8.55 kg |
| Groundwater resistant from lower edge of base section | 3 mm |
| Cutout dimension, width | 750 mm |
| Cutout dimension, length | 750 mm |
| Vertical drop between inlet and outlet | 8 mm |
| Installation depth | 287\|410 mm |
| Type of height adjustability | vertically adjustable upper section |
| Length | 444 mm |
| Width | 444 mm |
| Packaging dimension: length | 586 mm |
| Packaging dimension: width | 486 mm |
| Packaging dimension: height | 496 mm |

## Coverage features

| | |
|---|---|
| Type of cover | tileable cover plate |
| Cover material | Polymer |
| Width of cover | 366 mm |
| Length of cover | 366 mm |
| Locking | Lock & Lift |
| Load class | K 3 (EN 1253-1) |
| Tightness | surface water resistant |
| Max. flooring height | 16 mm |