Data sheet

Backwater valve Staufix DN 90, Floor slab, tileable, Type 2



Article information

article number: 730090.10X
EAN code: 4026092076323
Price group: 10

Product advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

Description

The backwater valve for wastewater with and without sewage (ÖNORM Austria) is equipped with two mechanical flaps that close automatically in the event of backwater. One flap also serves as a manually lockable emergency closure. Thanks to the modular KESSEL system, existing systems can be easily converted to the StaufixControl backwater valve.

General features

Colour	black
Standard	EN 13564
Nominal size (DN)	90
Outer diameter (OD)	90 mm
Type of wastewater	containing faecal matter (excepterion: Germany faecal-free)
Installation situation	floor slab installation
Delivery state	Installation-ready (connection parts must be connected on site)
Backwater protection	Type 2
Tightness	surface water resistant

Version

Stainless steel flap as rat protection	no
Emergency closure	yes
Mechanical backwater flaps	2

Dimensions

Net weight	5.92 kg
Gross weight	8.5 kg
Groundwater resistant from lower edge of base section	3 mm
Cutout dimension, width	750 mm
Cutout dimension, length	750 mm
Vertical drop between inlet and outlet	8 mm
Installation depth	287|410 mm
Type of height adjustability	vertically adjustable upper section
Length	444 mm
Width	444 mm
Packaging dimension: length	586 mm
Packaging dimension: width	486 mm
Packaging dimension: height	496 mm

Coverage features

Type of cover	tileable cover plate
Cover material	Polymer
Width of cover	366 mm
Length of cover	366 mm
Locking	Lock & Lift
Load class	K 3 (EN 1253-1)
Tightness	surface water resistant
Max. flooring height	16 mm