


Data sheet

Backwater valve Staufix DN 125, Floor slab, black, Type 2



Article information

article number: 730125.10S
 EAN code: 4026092076422
 Price group: 10

Product advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

General features

Colour	black
Standard	EN 13564
Nominal size (DN)	125
Outer diameter (OD)	125 mm
Type of wastewater	without sewage
Installation situation	floor slab installation
Delivery state	Installation-ready (connection parts must be connected on site)
Backwater protection	Type 2
Tightness	surface water resistant

Version

Stainless steel flap as rat protection	no
Emergency closure	yes
Mechanical backwater flaps	2

Dimensions

Net weight	8.3 kg
Gross weight	11.9 kg
Groundwater resistant from lower edge of base section	3 mm
Cutout dimension, width	750 mm
Cutout dimension, length	750 mm
Vertical drop between inlet and outlet	8 mm
Installation depth	341 464 mm
Type of height adjustability	vertically adjustable upper section
Length	511 mm
Width	444 mm
Packaging dimension: length	586 mm
Packaging dimension: width	486 mm
Packaging dimension: height	496 mm

Coverage features

Type of cover

Cover material

Colour of cover

Width of cover

Length of cover

Locking

Load class

Tightness

Cover plate

Polymer

black

366 mm

366 mm

Lock & Lift

L 15 (EN 1253-1)

surface water resistant