Data sheet

Backwater valve Staufix DN 150, exposed, Type 2



Article information

article number: 730150
EAN code: 4026092076477
Price group: 10

Product advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

Description

The backwater valve for wastewater with and without sewage (ÖNORM Austria) is equipped with two mechanical flaps that close automatically in the event of backwater. One flap also serves as a manually lockable emergency closure. Thanks to the modular KESSEL system, existing systems can be easily converted to the StaufixControl backwater valve.

General features

Colour	black
Standard	EN 13564
Nominal size (DN)	150
Outer diameter (OD)	160 mm
Type of wastewater	containing faecal matter (excepterion: Germany faecal-free)
Installation situation	exposed drainage pipe
Delivery state	installation-ready
Backwater protection	Type 2

Version

Stainless steel flap as rat protection	no
Emergency closure	yes
Mechanical backwater flaps	2

Dimensions

Net weight	3.41 kg
Gross weight	4.09 kg
Vertical drop between inlet and outlet	8 mm
Length	526 mm
Width	214 mm
Height	306 mm
Packaging dimension: length	524 mm
Packaging dimension: width	222 mm
Packaging dimension: height	265 mm

Coverage features

Type of cover	Lockable cover
Cover locking	One-handed closure