Data sheet

Yard drain System 400, DN 100, B, 380 - 510 mm

Article information
article number: 851100B
EAN code: 4026092004265
Price group: 10

Product advantages
- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description
The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

General features

Colour	black
Standard	EN 752
Nominal size (DN)	100
Outer diameter (OD)	110 mm
Odour trap	no

Version

System	400
Heating	without
Contents of sludge trap	yes
Discharge rate (l/s) with 20 mm threshold	4.5

Dimensions

Net weight	12.5 kg
Gross weight	12.5 kg
Groundwater resistant from lower edge of base section	500 mm
Cutout dimension, width	535 mm
Cutout dimension, length	585 mm
Min. insertion depth	55 mm
Installation depth	380|510 mm
Type of height adjustability	vertically adjustable upper section
Packaging dimension: length	585 mm
Packaging dimension: width	535 mm
Packaging dimension: height	510 mm

Tank/drain body

Number of outlets	1
Material of drain body	Polymer
Socket version	lateral

Coverage features

Type of cover	Round slotted cover
Cover material	Grey iron
Colour of cover	black
Width of cover	400 mm
Length of cover	400 mm
Surface	EDM
Load class	B 125 (EN 124)
Rim width	400 mm
Rim length	400 mm
Shape of upper section	square
Contents of sludge trap	yes