Data sheet

Yard drain System 400, DN 100, D, 730 - 1080 mm

Article information

article number: 851102D
EAN code: 4026092004333
Price group: 10

Product advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

General features

Colour	black
Standard	EN 752
Nominal size (DN)	100
Outer diameter (OD)	110 mm
Odour trap	included

Version

System	400
Heating	without
Contents of sludge trap	yes
Sealing water height	100 mm
Discharge rate (l/s) with 20 mm threshold	4.5

Dimensions

Net weight	43 kg
Gross weight	49 kg
Groundwater resistant from lower edge of base section	500 mm
Cutout dimension, width	535 mm
Cutout dimension, length	585 mm
Min. insertion depth	55 mm
Installation depth	730|1080 mm
Type of height adjustability	vertically adjustable upper section
Packaging dimension: length	585 mm
Packaging dimension: width	535 mm
Packaging dimension: height	1080 mm

Tank/drain body

Number of outlets	1
Material of drain body	Polymer
Socket version	lateral

Coverage features

Type of cover	Round slotted cover
Cover material	Grey iron
Colour of cover	black
Width of cover	450 mm
Length of cover	450 mm
Surface	EDM
Load class	D 400 (EN 124)
Rim width	450 mm
Rim length	450 mm
Shape of upper section	square
Contents of sludge trap	yes