Data sheet

Yard drain System 400, DN 150, B, 580-710 mm



Article information

article number: 851151B
EAN code: 4026092004388
Price group: 10

Product advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

General features

Colour	black
Standard	EN 752
Nominal size (DN)	150
Outer diameter (OD)	160 mm
Odour trap	included

Version

System	400
Heating	without
Contents of sludge trap	yes
Waterproofing layer on the upper section	Connection flange
Discharge rate (l/s) with 20 mm threshold	4.5

Dimensions

Vertical adjustment	55|180 mm
Net weight	23 kg
Gross weight	23 kg
Groundwater resistant from lower edge of base section	500 mm
Cutout dimension, width	535 mm
Cutout dimension, length	585 mm
Min. insertion depth	55 mm
Adjustment range	55|185
Installation depth	580|710 mm
Type of height adjustability	vertically adjustable upper section
Length	563 mm
Width	500 mm
Height	580 mm
Packaging dimension: length	700 mm
Packaging dimension: width	800 mm
Packaging dimension: height	610 mm

Tank/drain body

Number of outlets	1
Material of drain body	Polymer
Socket version	lateral

Coverage features

Type of cover	Round slotted cover
Cover material	Grey iron
Width of cover	400 mm
Length of cover	400 mm
Load class	B 125 (EN 124)
Rim width	400 mm
Rim length	400 mm
Shape of upper section	square
Contents of sludge trap	yes