Data sheet

Screw pumping station Aquaraize L Mono, 20 m3/h

Article information
article number: 918120
EAN code
Price group: 60

Product advantages

Description
Wastewater lifting station with storage tank for pumping special media (greasy water).

System consisting of:
- HPDE storage tank, odour-tight, for installation in frost-protected rooms, cover made of Duroplast 2K, with a quick-release closure
- Inlet DN 100/OD110 mm
- with ventilation socket DN100/OD110 mm
- with suction connection DN100/OD110 mm
- with discharge connection DN80/OD90 mm
- with integrated stainless steel sludge bucket (hole diameter 5 mm)
- 1 eccentric screw pump BN 30-6LT
- with non-return flap
- Electrical control unit for wall mounting in dry, frost-protected rooms, splashwater-proof, fully automatic pump control with optical and acoustic alarm signal, detailed operating and fault display, manual-0-
automatic switch,
with potential-free contact.
- with compressor set for air beading

Tank dimensions (tank dimensions are adapted to local conditions and defined in the release drawing)
Sample tank:
Length: 1130 mm
Width: 860 mm
Height: 1040 mm
Inlet height: 500 mm
Minimum inlet depth: 300 mm

General features

System type	Mono

Version

Type of system	Single unit

Dimensions

Net weight	135 kg
Gross weight	135 kg
Packaging dimension: length	0 mm
Packaging dimension: width	0 mm
Packaging dimension: height	0 mm

Pumping device

Protection class (pump)	IP 55
Max. pumping capacity	20 m^3/h
Power P1	3 kW

Control

Control unit	yes
Mains frequency	50 Hz