Data sheet

Screw pumping station Aquaraize S Duo, 6 m3/h

Article information
article number: 918206
EAN code
Price group: 60

Product advantages

Description
Wastewater lifting station with a storage tank for pumping special media (greasy water).

System consisting of:

- HPDE storage tank, odour-tight, for installation in frost-protected rooms, cover made of Duroplast 2K, with a quick-release closure
- Inlet DN 100 / DA 110 mm
- With a vent nozzle DN 100 / OD 110 mm
- With a suction nozzle DN 100 / OD 110 mm
- With a pressure nozzle DN 80 / OD 90 mm
- With an integrated stainless steel sludge bucket (hole diameter 5 mm)
- 2 eccentric screw pumps BN 30-6LT
- With non-return flaps DN 80 Electrical control unit for wall mounting in dry, frost-protected rooms, splashwater-proof, fully automatic pump control with optical and acoustic alarm signal, detailed operating and fault display, manual-0-automatic switch, with potential-free contact.
- With a compressor set for air beading

General features

System type	Duo

Version

Type of system	duo pump

Dimensions

Net weight	0 kg
Gross weight	175 kg
Packaging dimension: length	0 mm
Packaging dimension: width	0 mm
Packaging dimension: height	0 mm

Tank/drain body

Venting connection (DN)	100
Inlet nominal size (DN)	100

Pumping device

Protection class (pump)	IP 55
Max. pumping capacity	6 m^3/h
Power P1	1.1 kW

Control

Control unit	yes
Mains frequency	50 Hz