Data sheet

# Chamber module LW 1000 ground Access LW 600, 1380-1629 mm, Class A/B




## Article information

article number: 8740024
EAN code: 4026092065396
Price group: 60

## Product advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

## Description

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

## General features

| | |
|---|---|
| Colour | black |
| Material | PE-HD |
| Standard | EN 13598-2 |
| Installation situation | underground installation |
| Delivery state | Partly for on-site assembly (access steps have been pre-mounted in the factory) |
| Approval | Z-42.1-527 |
| Tightness | surface water resistant |

## Dimensions

| | |
|---|---|
| Net weight | 93.5 kg |
| Gross weight | 110 kg |
| Groundwater resistant from lower edge of base section | 3000 mm |
| Installation depth | 1380\|1629 mm |
| Type of height adjustability | vertically adjustable upper section |
| Length | 1200 mm |
| Width | 1200 mm |
| Packaging dimension: length | 1200 mm |
| Packaging dimension: width | 1200 mm |
| Packaging dimension: height | 2200 mm |

## Tank/drain body

| | |
|---|---|
| Inlet max. scoring (DN) | 150 |
| Clear width of tank (LW) | 1000 mm |
| Clear width of entry (LW) | 600 mm |

## Coverage features

| | |
|---|---|
| Type of cover | Round cover plate |
| Cover material | Grey iron |
| Colour of cover | black |
| Width of cover | 648 mm |
| Height of cover | 95 mm |
| Length of cover | 648 mm |
| Surface | Grey iron |
| Locking | unlocked |
| Load class | B 125 (EN 124) |
| Tightness | surface water resistant |