Data sheet

Chamber module LW 1000 ground Access LW 800, 2625-2874 mm, Class K 3



Article information

article number: 8740131
EAN code: 4026092071670
Price group: 60

Product advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

General features

Colour	black
Material	PE-HD
Standard	EN 13598-2
Installation situation	underground installation
Delivery state	Partly for on-site assembly (access steps have been pre-mounted in the factory)
Approval	Z-42.1-527
Tightness	surface water resistant

Dimensions

Net weight	202.56 kg
Gross weight	241.2 kg
Groundwater resistant from lower edge of base section	3000 mm
Installation depth	2625|2874 mm
Type of height adjustability	vertically adjustable upper section
Length	1200 mm
Width	1200 mm
Packaging dimension: length	2400 mm
Packaging dimension: width	1200 mm
Packaging dimension: height	2200 mm

Tank/drain body

Inlet max. scoring (DN)	150
Clear width of tank (LW)	1000 mm
Clear width of entry (LW)	800 mm

Coverage features

Type of cover	Round cover plate
Cover material	Stainless steel
Width of cover	960 mm
Height of cover	19 mm
Length of cover	960 mm
Surface	anti-slip
Locking	screwed
Load class	K 3 (EN 1253-1)
Tightness	surface water resistant