Data sheet

Ecolift XL backwater lifting st. Duo, 1 motor-driven flap, SPF 1400-S3

Article information
article number: 8741022
EAN code: 4026092068397
Price group: 60

Product advantages
- Wastewater drainage without interruption, even if a power failure occurs, as long as there is no backwater
- low pump use
- minimised noise emissions

Description
The backwater lifting station for faecal and non-faecal wastewater is equipped with two submersible pumps, one motor-driven and one mechanical closure system and a backflow preventer. The collection tank made of permanently resistant polymer (PE) has an enclosed pump tank. Quick-release closures enable the integrated components to be removed easily. Normally, draining takes place via the natural fall to the sewer. Backwater is detected by an optical probe, which causes the motor-driven closure system to close automatically and there is no longer free passage to the sewer. During the backwater phase, the water drains via a pressure pipe, which carries the wastewater into the sewer. The pressure pipe is a welded PE pipe; with pump SPF 4500, the pressure pipe must also be continued up to a pressure release chamber. The KESSEL modular system provides different upper sections and engineering chamber options as accessories.

General features

Colour	black
Standard	ÖNORM B 2501
Type of wastewater	for wastewater with and without sewage
Installation situation	free-standing installation
Delivery state	Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected)
Backwater protection	Type 3
Approval	Z-53.2-493,Z-53.2-493_V

Version

Note on installation depth	Version for deeper installation
Type of system	duo pump
Shut-off valve	Shut-off valve made of polymer
Passage seal for conduit pipe (DN)	100
Passage seal for ventilation pipe (DN)	70
Pump control	Control unit
Backflow preventer	integrated
Pressure pipe connection	horizontal
Motor-driven backwater flaps	1
Mechanical backwater flaps	1

Dimensions

Net weight	136.92 kg
Gross weight	162.7 kg
Groundwater resistant from lower edge of base section	3000 mm
Vertical drop between inlet and outlet	15 mm
Length	1384 mm
Width	1200 mm
Height	695 mm
Packaging dimension: length	2000 mm
Packaging dimension: width	1300 mm
Packaging dimension: height	950 mm

Tank/drain body

Nominal pressure (PN)	10
Pressure pipe connection (DN)	80
Pressure pipe connection (OD)	90 mm
Channel	continuous channel
Venting connection (DN)	70
Distance pipe bottom outlet to tank bottom	120 mm
Distance pipe bottom inlet to tank bottom	135 mm
Number of outlets	1
Outlet nominal size (DN)	150
Inlet nominal size (DN)	150
Number of inlets	1
Clear width of tank (LW)	1000 mm
Pumping volume	20 l
Tank volume	65.00 l

Pumping device

Pump	SPF 1400-S3 EcoXL
Number of pumps	2
Weight, pump	25 kg
Connection type	coded plug
Protection class	I
Insulation class	F
Cos phi - power factor	0.98
Protection class (pump)	IP 68 (3m/48h)
Temperature monitoring	integrated
Max. temperature (permanent) of conveyed material	40 °C
Max. pumping capacity	28 m^3/h
Max. pumping height	7.5 m
Speed	1370 U/min
Power P1	1.6 kW
Power P2	1.1 kW
Operating mode	S3 - 50 %
Type of pump connection cable	H07RN-F 7G 1.5 mm^2
Impeller type	Multi-vane impeller
Free passage	40 mm
Length of mains cable for pump	10 m
Rated current	7,3| A

Pumping capacity



Control

Control unit	Comfort Plus
Operating voltage	230 V
Rated current (max.)	|
Protection class control unit	IP 54
Type of fuse required (control unit)	C 16 A
Self-diagnosis system (SDS)	yes
Battery buffering	yes
Multi-line display	yes
Log book function	yes
Potential-free contact	yes
Alarm sensor	optical probe
Level measurement instrument	Immersion pipe
Type of level measurement	pneumatic
USB interface	yes
Standby power	5 W
Connection type	coded plug
Length of mains cable for control unit	1.6 m
GSM interface	yes