Data sheet

Pumping station Aquapump XL Duo, SPF 1400-S3, DO



Article information

article number: 8742016
EAN code: 4026092069523
Price group: 60

Product advantages

- Maximum safety
- Flexible installation
- Hygienic advantages for maintenance and repair

Description

The pumping station for wastewater with and without sewage is equipped with one or two submersible pumps, a backflow preventer and a shut-off valve for the pressure pipe. The collection tank made of permanently resistant polymer (PE) has a closed pump tank (dry installation) with a screwed-on access cover.

The station is controlled by a user-friendly control unit.

The KESSEL modular system provides different upper sections and engineering chamber options as accessories.

General features

Colour	black
Standard	EN 12050-1
Type of wastewater	with sewage
Installation situation	underground installation
Delivery state	Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected)
System type	Duo

Version

Note on installation depth	Version with lowest installation height
Type of system	duo pump
Shut-off valve	Shut-off valve made of polymer
Access steps	yes
Installation	Dry installation
Pump control	Control unit
Backflow preventer	integrated
Pressure pipe connection	horizontal

Dimensions

Net weight	212 kg
Gross weight	235 kg
Groundwater resistant from lower edge of base section	3000 mm
Length	1295 mm
Width	1295 mm
Height	1500 mm
Packaging dimension: length	2000 mm
Packaging dimension: width	1300 mm
Packaging dimension: height	1435 mm

Tank/drain body

Pressure pipe connection (DN)	80
Pressure pipe connection (OD)	90 mm
Venting connection (DN)	70
Distance from centre of outlet pipe to tank bottom	1343 mm
Distance pipe bottom inlet to tank bottom	753 mm
Distance from centre of inlet pipe to tank bottom	833 mm
Distance from inlet pipe invert to top of tank	747 mm
Inlet nominal size (OD)	160 mm
Inlet nominal size (DN)	150
Number of inlets	1
Clear width of tank (LW)	1000 mm
Clear width of entry (LW)	800 mm
Pumping volume	160 l
Tank volume	335.00 l

Pumping device

Pump	SPF 1400-S3
Number of pumps	2
Weight, pump	25 kg
Connection type	coded plug
Protection class	I
Insulation class	F
Cos phi - power factor	0.98
Protection class (pump)	IP 68 (3m/48h)
Temperature monitoring	integrated
Max. temperature (permanent) of conveyed material	40 °C
Max. pumping capacity	38 m³/h
Max. pumping height	7 m
Speed	1370 U/min
Power P1	1.6 kW
Power P2	1.1 kW
Operating mode	S3 - 50 %
Type of pump connection cable	H07RN-F 3G 1.5 mm²
Impeller type	Multi-vane impeller
Free passage	40 mm
Length of mains cable for pump	10 m
Rated current	7,3| A

Pumping capacity



Control

Control unit	Comfort
Operating voltage	230 V
Rated current (max.)	|
Protection class control unit	IP 54
Self-diagnosis system (SDS)	yes
Battery buffering	yes
Multi-line display	yes
Log book function	yes
Potential-free contact	optional
Alarm sensor	Immersion pipe
Level measurement instrument	Immersion pipe
Type of level measurement	pneumatic
USB interface	yes
Connection type	coded plug
Length of mains cable for control unit	1.4 m
GSM interface	yes