

## Shower channel Linearis Compact L: 550 mm, DN50, enclWPM, 304SSTcov, K3



## **Article information**

Item no.: 45600.61 GTIN: 4026092048177 Price group: 10

## **Advantages**

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

## Description

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

| Variant                                    |   |
|--|---|
| System:                                    | 125   |
| Seepage opening:                           | prepared  |
| Waterproofing layer on the upper section:  | Enclosed sealing collar to be glued (bd) according to |
|  | DIN 18534   |
| Water exposure class in accordance to DIN  | W2-I  |
| 18534-1 (up to and including):             |   |
| Sealing water height:                      | 22 mm   |
| Discharge rate (l/s) with 10 mm threshold: | 0,6   |
| Discharge rate (l/s) with 20 mm threshold: | 0,7   |
| Discharge rate (l/s) without threshold:    | 0,5 mm  |
|  |   |
| General characteristics                    |   |
| Nominal size (DN):                         | 50  |
| Outer diameter (OD):                       | 50 mm   |
| Odour trap:                                | included  |
|  |   |
| Dimensions                                 | 1.001   |
| Net weight:                                | 1,66 kg   |
| Gross weight:                              | 2,04 kg   |
| Outer dimension, length:                   | 615 mm  |
| Installation depth:                        | 80 - 140 mm   |
| Width:                                     | 191 mm  |
| Height:                                    | 80 mm   |
| Packaging dimension:                       | length  |



Packaging dimension: Packaging dimension:

Tank/drain body Number of outlets: Material of drain body:

Coverage features Type of cover: Cover material: Colour of cover: Surface: Frame material: Load class: Grating design: Rim width: Rim length: Max. flooring height: Shape of upper section: Upper section material: width height

1 ABS

Stainless steel cover Stainless steel 14301 silver Brushed SST Stainless steel 14301 K 3 (EN 1253-1) optionally tileable 66 mm 550 mm 15 mm square ABS