


## Shower channel Linearis Compact L: 650 mm, DN50, enclWPM, 304 STcov, K3



### Article information

Item no.: 45600.62  
GTIN: 4026092048184  
Price group: 10

### Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

### Description

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

Variant	
System:	125
SonicControl:	prepared
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Water supply:	W2-I
Sealing water height:	22 mm
Discharge rate (l/s) with 10 mm backwater:	0,6
Discharge rate (l/s) with 20 mm backwater:	0,7
Discharge rate (l/s) without backwater:	0,5 mm
General characteristics	
Nominal size (DN):	50
Outer diameter (OD):	50 mm
purchasable by service partner:	No
Dimensions	
Net weight:	1,85 kg
Gross weight:	2,22 kg
Outer dimension, length:	715 mm
Installation depth:	80 - 140 mm
Width:	191 mm
Height:	80 mm
Packaging dimension:	length
Packaging dimension:	width

Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	ABS
Coverage features	
Type of cover:	Stainless steel cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Frame material:	Stainless steel 14301
Cover locking:	placed
Load class:	K 3 (EN 1253-1)
Grating colour:	optionally tileable
Rim length:	66 mm
Rim material:	650 mm
Max. flooring height:	15 mm
Upper section material:	ABS
Odour trap:	included