

Shower channel Linearis Compact L: 950 mm, DN50, enclWPM, 304SSTcov, K3



Article information

Item no.: 45600.65 GTIN: 4026092046104

Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Ready-to-install complete set

Description

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

Variant

System: 125 Seepage opening: prepared

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

W2-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height: 22 mm Discharge rate (l/s) with 10 mm threshold: 0,6 Discharge rate (l/s) with 20 mm threshold: 0,7 Discharge rate (l/s) without threshold: 0,5 mm

General characteristics

Nominal size (DN): 50
Outer diameter (OD): 50 mm
Odour trap: included

Dimensions

Net weight:2,44 kgGross weight:2,96 kgOuter dimension, length:1015 mmInstallation depth:80 - 140 mmWidth:191 mmHeight:80 mmPackaging dimension:length



Packaging dimension: width Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS

Coverage features

Type of cover: Stainless steel cover Cover material: Stainless steel 14301

Colour of cover: silver

Frame material: Stainless steel 14301

Load class: K 3 (EN 1253-1)
Grating design: optionally tileable

Rim width: 66 mm
Rim length: 950 mm
Max. flooring height: 15 mm
Upper section material: ABS