



## Ecoguss project drain DN 100, vert., Variofix, Slotted cover





## Article information

Item no.: 48411.51 GTIN: 4026092034330 Price group: 40

## **Advantages**

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

## **Description**

The Ecoguss project drain with connection flange is used for point drainage and is equipped with a removable odour trap as well as a lip seal and a temporary protective cover. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant	125
System:	Enclosed sealing collar to be glued (bd) according to
Waterproofing layer on the upper section:	DIN 18534
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	50 mm
General characteristics	EN 1253-1
Standard:	100
Nominal size (DN):	110mm
Outer diameter (OD):	Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-17
Approval:	19_V
Odour trap:	included
Dimensions Net weight:	3,14 kg



Gross weight: Diameter: Type of height adjustability: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension: Tank/drain body Number of outlets: Material of drain body: Socket version: Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Min. flooring height: Frame material: Locking: Load class: Rim width: Rim length: Max. flooring height: Upper section:

Upper section material:

3,9 kg 135 mm vertically adjustable upper section 135 mm 135 mm length width height 1 Ecoguss resistant vertical Slotted cover Stainless steel 14301 silver 138 mm 138 mm 10 mm Stainless steel 14301 screwed K 3 (EN 1253-1)

adjustable in three dimensions

150 mm

150 mm

17 mm

ABS