



Variofix upper section Slotted cover, 304 SST, anti-slip, L 15





Article information

Item no.: 48907

GTIN: 4026092053690

Price group: 70

Advantages

- Different covers selectable
- Including waterproofing membrane

Description

Used in combination with a drain body of the KESSEL modular system, the upper section is suitable for indoor point drainage.

Variant

System: 125 Seal: Lip seal

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Water exposure class in accordance to DIN

18534-1 (up to and including):

W3-I

General characteristics

Sustainable: through the use of recycled material

Dimensions

Vertical adjustment: 10 - 18 mm
Net weight: 1,57 kg
Gross weight: 1,96 kg
Diameter: 312 mm

Type of height adjustability: vertically adjustable upper section

Height: 120 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height



Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover: silver

Frame material: Stainless steel 14301

Locking: screwed

Load class: L 15 (EN 1253-1)

Grating design: Kessel

Slip resistance class: R11 according to DIN 51130; C according to DIN

51097

Rim width: 150 mm Rim length: 150 mm

Upper section: adjustable in three dimensions

Shape of upper section: square Upper section material: ABS