

Yard drain System 100, vert., slot grat., B 125



Article information

Item no.: 67110B

GTIN: 4026092039373

Price group: 10

Advantages

- Recyclable
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

Variant

System: 100 Contents of sludge trap: yes

General characteristics

Nominal size (DN): 100 Odour trap: no

Dimensions

Net weight:2,9 kgGross weight:2,9 kgPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Number of outlets:

Material of drain body: Ecoguss Heavy Duty

Socket version: vertical

Coverage features

Type of cover: Round slotted cover

Cover material: Ecoguss
Colour of cover: black



Width of cover: 247 mm
Length of cover: 247 mm
Surface: EDM

Locking: Lock & Lift
Load class: B 125 (EN 124)

Shape of upper section: square Contents of sludge trap: yes