

## Pump drive SPF 4500 400 V, S3, 10 m cable



### Article information

Item no.: 680442  
 GTIN: 4026092072851  
 Price group: 90

### Description

Pump drive with multi-vane impeller for faecal wastewater

#### General characteristics

Type of wastewater: with sewage

#### Dimensions

Net weight: 26 kg  
 Gross weight: 29,3 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: SPF 4500-S3  
 Connection type: Direct connection  
 Operating voltage: 400 V  
 Protection class: I  
 Run dry safe: yes  
 Protection class (pump): IP 68 (3m/48h)  
 Temperature monitoring: controlled via control unit  
 Max. temperature (permanent) of conveyed material: 40 °C  
 Max. pumping height: 20 m  
 Speed: 2850 U/min  
 Power P1: 4,5 kW  
 Power P2: 3,5 kW  
 Operating mode: S3 - 50 %  
 Type of pump connection cable: H07RN-F 7G 1.5 mm<sup>2</sup>  
 Length of mains cable for pump: 10 m  
 Rated current: 7,5 A

#### Control

Mains frequency: 50 Hz

Operating voltage:  
Connection type:

400 V  
Direct connection