IK KESSEL

Controlfix clean out DN 150, Floor slab, black





Article information

Item no.: 80150S GTIN: 4026092004098 Price group: 30

Advantages

- Simple conversion to Staufix SWA
- Fast, simple and toolless maintenance
- Quick and toolless access for cleaning

Description

The Premium clean out for faecal and faecal-free wastewater makes easy access to wastewater pipes possible for inspection and maintenance work. Thanks to the modular KESSEL system, existing systems can easily be converted to a Staufix SWA Premium backwater valve, Staufix FKA or Pumpfix F backwater pumping station.

General characteristics	black
Colour:	150
Nominal size (DN):	160 mm
Outer diameter (OD):	for wastewater with and without sewage
Type of wastewater:	floor slab installation
Installation situation:	Installation-ready (connection parts must be
Delivery state:	connected on site)
Dimensions Net weight: Gross weight: Groundwater resistant from lower edge of base section:	14 kg 17,32 kg 3000 mm
Cutout dimension, width:	750 mm
Cutout dimension, length:	750 mm
Vertical drop between inlet and outlet:	9 mm
Installation depth:	516 - 669 mm
Type of height adjustability:	vertically adjustable upper section
Length:	486 mm



Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Locking: Load class: Tightness: 590 mm length width height

including spigot and socket

Cover plate Polymer black 366 mm 366 mm Lock & Lift L 15 (EN 1253-1) surface water resistant