

Grease separator EasyClean free NS 3, Standard



Article information

Item no.: 93003.01 GTIN: 4026092060889 Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant Disposal variant: Shredder-Mix-System: Inspection window: Nominal size (NS): SonicControl: Refill inlet in accordance with DIN 1988: Type of disposal: Load-bearing capacity (DIN 19901):	Standard no 3 no no manual with suction hose F3
General characteristics Material: Installation situation: Delivery state:	PE free-standing installation Installation-ready (connection parts must be connected on site)
Dimensions Net weight: Gross weight: Set-up area, length: Set-up area, width: Set-up area, height:	87 kg 117 kg 1736 mm 674 mm 1434 mm



Required access area, length:	1500 mm
Required access area, width:	674 mm
Required access area, height:	1434 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	985 mm
Distance pipe bottom inlet to tank bottom:	1055 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (OD):	110 mm
Inlet nominal size (DN):	100 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes
	in accordance with DIN 19560, PP or AS
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Locking:	Quick-release closure
Tightness:	odour-tight
Wastewater contents	
Separator contents:	300 l
Total volume:	600 l
Contents of sludge trap:	300 l
Storage quantity of grease:	120 l
Control	
Control unit:	no