

Lifting stati. Aqualift F XL 300l Mono, SPF 3000-S3, shut-off valve



Article information

Item no.: 11047
GTIN: 4026092057148
Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

| | |
|---------------------------|--------------------------------|
| Type of system: | Single unit |
| Shut-off valve: | Shut-off valve made of polymer |
| Pressure pipe connection: | horizontal |

General characteristics

| | |
|-------------------------|----------------------------|
| Colour: | black |
| Standard: | EN 12050-1 |
| Type of wastewater: | with sewage |
| Installation situation: | free-standing installation |
| System type: | Mono |

Dimensions

| | |
|----------------------|----------|
| Net weight: | 76,69 kg |
| Gross weight: | 96,69 kg |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Packaging dimension: | length |

Tank/drain body

| | |
|--------------|-------|
| Tank volume: | 300 l |
|--------------|-------|

Pumping device

| | |
|---------------|----------|
| Pump control: | SPF 3000 |
|---------------|----------|

| | |
|---------------------------------|---------------------|
| Number of pumps: | 1 |
| Length of mains cable for pump: | 5 m |
| Operating mode: | S3 - 50 % |
| Impeller type: | Multi-vane impeller |
| Free passage: | 40 mm |

| | |
|---------------------------------------|----------------|
| Control | |
| Level measurement instrument: | Immersion pipe |
| Type of level measurement: | pneumatic |
| Mains frequency: | 50 Hz |
| Operating voltage: | 400 V |
| Max. permissible switching frequency: | Comfort |