


Ferrofix floor drain press, fl. Sys 200, horiz., Ladd grt, SST OT



Article information

Item no.: 142026.30
 GTIN: 4026092006696
 Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel

Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap, a lip seal and a temporary protective cover. The outlet socket is suitable for connection to SML cast iron pipes.

Variant

System:	200
Waterproofing layer on the upper section:	Connection flange
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	70 mm

General characteristics

Standard:	EN 1253-1
Nominal size (DN):	100
Outer diameter (OD):	110 mm

Dimensions

Net weight:	15 kg
Gross weight:	15 kg
Vertical adjustment:	vertically adjustable upper section
Width:	280 mm
Length:	280 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Tank/drain body

Number of outlets:	1
Material of drain body:	Stainless steel 14301
System:	lateral

Coverage features

Type of cover:	Ladder grating
----------------	----------------

Cover material:	Stainless steel 14301
Width of cover:	190 mm
Height of cover:	30 mm
Length of cover:	190 mm
Cover locking:	unlocked
Load class:	M 125 (EN 1253-1)
Rim length:	200 mm
Rim material:	200 mm
Upper section:	vertically adjustable
Upper section material:	Stainless steel 14301
Odour trap:	included