


## Shell Kit for Ecolift, w/o socket, black cover





## Article information

Item no.: 21000S-RBK GTIN: 4026092097137 Price group: 20

## Description

KESSEL shell kit for Ecolift, without sockets, black cover

Shell kit consisting of a drain body, upper section and flange for joint sealing. The inlet and outlet sockets are not included.

For combination with a KESSEL technology kit for creating an Ecolift backwater lifting station.

General characteristics	
Colour:	black
Type of wastewater:	with sewage
Installation situation:	floor slab installation
Delivery state:	Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected)
Approval:	Z-53.2-487
Motor type:	KSM 140
Type de protection moteur:	IP 68 (3m/48h)
Dimensions	
Net weight:	25 kg
Gross weight:	30,5 kg
Groundwater resistant from lower edge of base section:	3000 mm



Installation depth: Type of height adjustability: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Nominal pressure (PN): Pressure pipe connection (OD): Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Drainage function: Locking: Load class:

ŝ,

516 - 669 mm vertically adjustable upper section 590 mm length width height

6 40 mm optional

Cover plate with slotted cover Polymer black 366 mm 366 mm yes Lock & Lift L 15 (EN 1253-1)