

Drehfix basement drain DN 100, Black grating, Type 5





Article information

Item no.: 27301
GTIN: 4026092007815
Price group: 10

Advantages

- Integrated backwater protection
- Simple
- toolless maintenance and cleaning

Description

The basement drain for faecal-free wastewater is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves at the same time as an emergency closure to be closed by hand.

Variant	
Contents of sludge trap:	yes
Emergency closure:	yes
Discharge rate (l/s) with 20 mm backwater:	1,8
Mechanical backwater flaps:	2
General characteristics	
Colour:	black
Standard:	EN 1253
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Type of wastewater:	without sewage
Installation situation:	floor slab installation
Delivery state:	installation-ready
Backwater protection:	Type 5
Dimensions	
Net weight:	1,49 kg
Gross weight:	1,51 kg
Cutout dimension, width:	190 mm
Cutout dimension, length:	320 mm

Installation depth:	210 - 240 mm
Vertical adjustment:	vertically adjustable upper section
Width:	168 mm
Length:	285 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Coverage features

Type of cover:	Slotted cover
Colour of cover:	black
Load class:	K 3 (EN 1253-1)
Backflow protection:	Polymer
Grid size, length:	black
Grating material:	190 mm
Grid size, width:	150 mm
Grid size, height:	14 mm
Contents of sludge trap:	yes
Odour trap:	included

Cover

Grid size, length:	black
Backflow protection:	Polymer
Grating material:	190 mm
Grid size, width:	150 mm
Grid size, height:	14 mm