

Drain body The Universal DN 100, 3 inlets, w. backwater valve



Article information

Item no.: 27600
GTIN: 4026092085141
Price group: 10

Advantages

- Flexible installation: vertically adjustable upper section rotatable
- Integrated backwater protection
- vertically adjustable

Description

The polymer drain body is equipped with a removable backwater valve with two backwater flaps, one hand-lockable emergency closure and a sludge bucket. The drain body also has two inlets DN 50 and one inlet DN 70 with blind plug. Material:

PP

Variant

Waterproof flange:
Waterproofing layer on the drain body:
Sealing water height:
Mechanical backwater flaps:

Pre-assembled at the factory
Connection flange
60 mm
2

General characteristics

Colour:
Standard:
Nominal size (DN):
Outer diameter (OD):
Type of wastewater:
Installation situation:
Delivery state:
Backwater protection:

black
EN 1253
100
110 mm
without sewage
floor slab installation
installation-ready
Type 5

Dimensions

Net weight:
Gross weight:
Vertical adjustment:
Width:
Height:
Length:

2,31 kg
2,31 kg
vertically adjustable upper section
285 mm
190 mm
380 mm

| | |
|-------------------------|----------|
| Packaging dimension: | width |
| Packaging dimension: | height |
| Packaging dimension: | length |
| Tank/drain body | |
| Material of drain body: | PP |
| System: | lateral |
| Coverage features | |
| Odour trap: | included |