


Drain body The Universal DN 100, Black grating, Backwater prot





Article information

Item no.: 27611 GTIN: 4026092007822 Price group: 10

Advantages

- Flexible installation: vertically adjustable upper section rotatable
- Integrated backwater protection
- vertically adjustable

Description

The polymer drain body is equipped with a removable backwater valve with two backwater flaps, one hand-lockable emergency closure and a sludge bucket. The drain body also has two inlets DN 50 and one inlet DN 70 with blind plug. Material:

Variant
Contents of sludge trap:
Emergency closure:
Waterproof flange:
Mechanical backwater flaps:

General characteristics Colour: Standard: Nominal size (DN): Outer diameter (OD): Type of wastewater: Installation situation: Delivery state: Backwater protection: Odour trap: Sustainable: PP

yes yes without 2 black EN 1253 100 110 mm without sewage floor slab installation installation-ready



Dimensions Net weight: Gross weight: Cutout dimension, width: Cutout dimension, length: Installation depth: Type of height adjustability: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Load class: Grid size, length: Grid size, width: Grid size, height: Contents of sludge trap:

Cover Grid size, length: Grid size, width: Grid size, height: 2,69 kg 3,02 kg 320 mm 400 mm 216 - 276 mm vertically adjustable upper section 380 mm 300 mm length width height

lateral

Slotted cover Polymer black K 3 (EN 1253-1) 188 mm 188 mm 25 mm yes

188 mm 188 mm 25 mm