


Universal Plus basement drain vertical, with backwater valve





Article information

Item no.: 27660

GTIN: 4026092096949

Price group: 10

Advantages

- Sustainable due to use of recycled material
- Inlets above the floor slab, no penetration required
- Vertical outlet for easy installation and easy access to the main drainage pipe

Description

In combination with an upper section, the polymer Universal Plus drain body is used for drainage of non-faecal wastewater and is equipped with a removable backwater valve with two backwater flaps, a one hand-lockable emergency closure and a sludge bucket. Including temporary protective cover.

Variant

Contents of sludge trap:

Emergency closure:

Waterproof flange:

Sealing water height:

Mechanical backwater flaps:

yes

without

60 mm

General characteristics

Colour: black
Standard: EN 1253
Nominal size (DN): 100

Type of wastewater: without sewage Installation situation: floor slab installation

Backwater protection: Type 5 Odour trap: no

Sustainable: through the use of recycled material

Dimensions



Net weight:1,85 kgGross weight:2,34 kgDiameter:235 mmCutout dimension, width:310 mmCutout dimension, length:310 mm

Type of height adjustability: vertically adjustable upper section

Height: 270 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Socket version: vertical

Coverage features

Contents of sludge trap: yes