


Submersible pump Aquadive KTP 300 without float switch, 10 m



Article information

Item no.: 28740
 GTIN: 4026092000908
 Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

KTP 300 submersible pump without float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Variant

Pump control: without float switch

General characteristics

Material: Polymer
 Standard: EN 12050-2
 Type of wastewater: without sewage
 Cable length: 10 m

Dimensions

Net weight: 4,33 kg
 Gross weight: 4,69 kg
 Length: 275 mm
 Width: 390 mm
 Height: 216 mm
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Wastewater contents	
Pressure pipe connection:	R 1 "
Pumping device	
Pump:	KTP 300
Number of pumps:	1
Weight, pump:	4 kg
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	1,6 A
Length of mains cable for pump:	10 m
Protection class:	I
Insulation class:	F
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	6 m
Speed:	2800 U/min
Power P1:	0,34 kW
Power P2:	0,21 kW
Operating mode:	S1
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Control	
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	1,6 A