


## Submersible pump Aquadive KTP 300 resistant, without float switch, 10 m



### Article information

Item no.: 28740C  
GTIN: 4026092094891  
Price group: 20

### Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

### Description

KTP 300 submersible pump without float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Variant

Resistant:

Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems integrated

Backflow preventer:

General characteristics

Type of wastewater:

without sewage

Cable length:

10 m

Dimensions

Net weight:

4,33 kg

Gross weight:

4,69 kg

Length:

275 mm

Width:

390 mm

Height:

216 mm

Packaging dimension:

length

Packaging dimension:

width

|  |                                |
|--|--------------------------------|
| Packaging dimension:                               | height                         |
| Pumping device                                     |                                |
| Pump:  | KTP 300 resistant              |
| Number of pumps:                                   | 1                              |
| Weight, pump:                                      | 4 kg                           |
| Connection type:                                   | Schuko (earthed contact) 2-pin |
| Operating voltage:                                 | 230 V                          |
| Protection class:                                  | I                              |
| Insulation class:                                  | F                              |
| Protection class (pump):                           | IP 68                          |
| Max. temperature (permanent) of conveyed material: | 40 °C                          |
| Hot water resistance for a short time (2 min):     | 80 °C                          |
| Max. pumping height:                               | 6 m                            |
| Speed:   | 2800 U/min                     |
| Power P1:  | 0,34 kW                        |
| Power P2:  | 0,21 kW                        |
| Operating mode:                                    | S1                             |
| Type of pump connection cable:                     | H07RN-F 3G 1.5 mm <sup>2</sup> |
| Impeller type:                                     | Multi-vane impeller            |
| Free passage:                                      | 10 mm                          |
| Length of mains cable for pump:                    | 10 m                           |
| Rated current:                                     | 1,9 A                          |
| Control  |                                |
| Mains frequency:                                   | 50 Hz                          |
| Operating voltage:                                 | 230 V                          |
| Connection type:                                   | Schuko (earthed contact) 2-pin |
| Type of fuse required (electrical protection):     | C 16 A                         |