


Submersible pump Aquadive KTP 300 resistant, without float switch, 10 m



Article information

Item no.: 28740C
GTIN: 4026092094891
Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

KTP 300 submersible pump without float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Variant

Resistant:

Resistant to waste water containing salt, softener and condensate

Backflow preventer:

integrated

General characteristics

Type of wastewater:

without sewage

Cable length:

10 m

Dimensions

Net weight:

4,33 kg

Gross weight:

4,69 kg

Length:

275 mm

Width:

390 mm

Height:

216 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Pumping device	
Pump:	KTP 300 resistant
Number of pumps:	1
Weight, pump:	4 kg
Connection type:	Schuko (earthed contact) 2-pin
Operating voltage:	230 V
Protection class:	I
Insulation class:	F
Protection class (pump):	IP 68
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	6 m
Speed:	2800 U/min
Power P1:	0,34 kW
Power P2:	0,21 kW
Operating mode:	S1
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	1,9 A
Control	
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin