

Submers. pump Aquadive GTF 1700 res., without float switch, 10 m, 230 V

Article information

Item no.: 28782C
GTIN: 4026092113691
Price group: 20

Description

Submersible pump Aquadive GTF1700, resistant, without float switch, 10m

The submersible pump for maximum operational safety, with longitudinally watertight moulded connection line and removable intake cage.

Variant

Resistant: Resistant to waste water containing salt, softener and condensate
Pump control: without float switch

General characteristics

Material: Polymer, Stainless steel
Standard: EN 12050-2
Type of wastewater: without sewage
Cable length: 10 m

Dimensions

Length: 240 mm
Width: 200 mm
Height: 377 mm

Tank/drain body

Pressure pipe connection: R 1 ¼"

Pumping device

Pump: GTF 1700
Weight, pump: 13,9 kg
Connection type: coded plug
Operating voltage: 230 V
Protection class: I
Insulation class: F
Cos phi - power factor: 0,97
Protection class (pump): IP 68 (3m)
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed material: 40 °C

Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	13 m
Speed:	2850 U/min
Power P1:	1,6 kW
Power P2:	1 kW
Operating mode:	S3 - 50 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	30 mm
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	7,3 A
Control	
Operating voltage:	230 V
Connection type:	coded plug
Mains frequency:	50 Hz