

Replacement pump KTP 300 for Minilift



Article information

Item no.: 28836
 GTIN: 4026092000922
 Price group: 90

Description

Replacement pump for sewage-free wastewater

Variant

Pump control: Float switch

General characteristics

Standard: EN 12050-2
 Type of wastewater: without sewage
 Cable length: 5 m

Dimensions

Net weight: 4,21 kg
 Gross weight: 4,49 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: KTP 300
 Connection type: Schuko (earthed contact) 2-pin
 Operating voltage: 230 V
 Mains frequency: 50 Hz
 Protection class: I
 Insulation class: F
 Protection class (pump): IP 68 (3m)
 Temperature monitoring: integrated
 Max. temperature (permanent) of conveyed material: 35 °C
 Max. pumping height: 6 m
 Speed: 2800 U/min
 Power P1: 0,34 kW
 Power P2: 0,21 kW
 Operating mode: S1

Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	5 m
Rated current:	1,9 A
Control	
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin